Instructions for the preparation of a 2-column format camera-ready paper in LaTeX for the Hyperon99 symposium

D. Jensen [a*] and E. Monnier[b]

[a]Fermi National Accelerator Laboratory,
P.O. Box 500 Batavia, IL 60510-500

[b]University of Chicago, Enrico Fermi Institute,
5640 S. Ellis Avenue, Chicago, Illinois, 60637

These pages provide you with an example of the layout and style for 100% reproduction which we wish you to adopt during the preparation of your paper. This is the output from the LaTeX document style and file given as an example. In the case that another document editor is used, which we would prefere not, please use the dimension and style guide line given in this document.

1. FORMAT

Text should be produced within the dimensions shown on these pages: each column 7.5 cm wide with 1 cm middle margin, total width of 16 cm and a maximum length of 21.7 cm on first pages and 22.5 cm on second and following pages. The LaTeX document style uses the maximal stipulated length apart from the following two exceptions (i) LaTeX does not begin a new section directly at the bottom of a page, but transfers the heading to the top of the next page; (ii) LaTeX never (well, hardly ever) exceeds the length of the text area in order to complete a section of text or a paragraph.

1.1. Spacing

We normally recommend the use of 1.0 (single) line spacing. However, when typing complicated mathematical text LaTeX automatically increases the space between text lines in order to prevent sub- and superscript fonts overlapping one another and making your printed matter illegible.

1.2. Fonts

These instructions have been produced using a 10 point Computer Modern Roman. Other recommended fonts are 10 point Times Roman, New Century Schoolbook, Bookman Light and Palatino.

*Footnotes should appear on the first page only to indicate your present address (if different from your normal address), research grant, sponsoring agency, etc. These are obtained with the `\thanks` command.

2. PRINTOUT

The most suitable printer is a laser printer. A dot matrix printer should only be used if it possesses an 18 or 24 pin printhead ("letter-quality").

The printout submitted should be an original; a photocopy is not acceptable. Please make use of good quality plain white US Letter (or A4) paper size. *The dimensions shown here should be strictly adhered to: do not make changes to these dimensions, which are determined by the document style.* The document style leaves at least 3 cm at the top and bottom of the page. The bottom of the page will contain the page number.

Printers sometimes produce text which contains light and dark streaks, or has considerable lighting variation either between left-hand and right-hand margins or between text heads and bottoms. To achieve optimal reproduction quality, the contrast of text lettering must be uniform, sharp and dark over the whole page and throughout the article.

If corrections are made to the text, print completely new replacement pages. The contrast on these pages should be consistent with the rest of the paper as should text dimensions and font sizes.

3. TABLES AND ILLUSTRATIONS

Tables should be made with LaTeX. Illustrations should be originals or sharp prints. They should be arranged throughout the text and preferably be included *on the same page as they are first discussed.* They should have a self-contained caption and be positioned

Table 1
Biologically treated effluents (mg/l)

	Pilot plant		Full scale plant	
	Influent	Effluent	Influent	Effluent
Total cyanide	6.5	0.35	2.0	0.30
Method-C cyanide	4.1	0.05		0.02
Thiocyanide	60.0	1.0	50.0	< 0.10
Ammonia	6.0	0.50		0.10
Copper	1.0	0.04	1.0	0.05
Suspended solids				< 10.0

Reprinted from: G.M. Ritcey, Tailings Management, Elsevier, Amsterdam, 1989, p. 635.

in flush-left alignment with the text margin within the column. If they do not fit into one column (using `\begin{table}[htbc]` or `\begin{figure}[htbc]`) they may be placed across both columns (using `\begin{table*}` or `\begin{figure*}` so that they appear at the top of a page).



Figure 1. Good sharp prints should be used and not (distorted) photocopies.

3.1. Tables

Tables should be presented in the form shown in Table 1. Their layout should be consistent throughout.

Horizontal lines should be placed above and below table headings, above the subheadings and at the end of the table above any notes. Vertical lines should be avoided.

If a table is too long to fit onto one page, the table number and headings should be repeated above the continuation of the table. For this you have to reset the table counter with `\addtocounter{table}{-1}`. Alternatively, the table can be turned by 90° ('landscape mode') and spread over two consecutive pages (first an even-numbered, then an odd-numbered one) created by means of `\begin{table}[h]` without a caption. To do this, you prepare the table as a separate LaTeX document and attach the tables to the empty pages with a few spots of suitable glue.

3.2. Figures

Figure should be presented in the form shown in figure 1. It is preferable that the figure be in encapsulated postscript format and be called within the LaTeXfile as shown in the example file. When placing a figure at the top of a page, the top of the figure should be at the same level as the bottom of the first text line. All notations and lettering should be no less than 2 mm high.

3.3. Line or computer drawings

In case of line drawings, they should be drawn in India ink on tracing paper with the aid of a stencil or should be glossy prints of the same. Computer prepared drawings are also acceptable. They should be attached to your manuscript page, correctly aligned, using suitable glue and *not transparent tape.*

3.4. Photographs

Photographs must always be sharp originals (*not screened versions*) and rich in contrast. They will undergo the same reduction as the text and should be pasted on your page in the same way as line drawings. Only black and white (or grayscale) photographs will be accepted.



Figure 2. Remember to keep details clear and large enough and to have the right size for the figure.

4. EQUATIONS

Equations should be flush-left with the text margin; LaTeX ensures that the equation is preceded and followed by one line of white space. LaTeX provides the document-style option `fleqn` to get the flush-left effect.

$$H_{\alpha\beta}(\omega) = E_{\alpha}^{(0)}(\omega)\delta_{\alpha\beta} + \langle\alpha|W_{\pi}|\beta\rangle \qquad (1)$$

You need not put in equation numbers, since this is taken care of automatically. The equation numbers are always consecutive and are printed in parentheses flush with the right-hand margin of the text and level with the last line of the equation. For multi-line equations, use the `eqnarray` environment. For complex mathematics, use the $\mathcal{AMS}$-LaTeX package.

REFERENCES

1. S. Scholes, Discuss. Faraday Soc. No. 50 (1970) 222.
2. O.V. Mazurin and E.A. Porai-Koshits (eds.), Phase Separation in Glass, North-Holland, Amsterdam, 1984.
3. Y. Dimitriev and E. Kashchieva, J. Mater. Sci. 10 (1975) 1419.
4. D.L. Eaton, Porous Glass Support Material, US Patent No. 3 904 422 (1975).

References should be collected at the end of your paper. Do not begin them on a new page unless this is absolutely necessary. They should be prepared according to the sequential numeric system making sure that all material mentioned is generally available to the reader. Use `\cite` to refer to the entries in the bibliography so that your accumulated list corresponds to the citations made in the text body.

Above we have listed some references according to the sequential numeric system [1–4].